

# city CREVE COEUR

300 North New Ballas Road • Creve Coeur, Missouri 63141 (314) 432-6000 • Fax (314) 872-2539 • Relay MO 1-800-735-2966 www.creve-coeur.org

### **NOTICE OF PUBLIC HEARING**

APPLICATION TO PLANNING AND ZONING COMMISSION #20-012: A CONDITIONAL USE PERMIT FOR VANTAGE CREDIT UNION WITH DRIVE-THROUGH FACILITIES AT 611 N. LINDBERGH BOULEVARD

FOR THE MEETING OF: Monday, May 18, 2020, at 6:30 PM.

**LOCATION:** 611 N. Lindbergh Boulevard, zoned District

**REQUEST:** Yosef Howley, of CEDC, on behalf of Vantage Credit Union, has submitted an application for conditional use permit for a new credit union facility with drive-through banking at 611 N. Lindbergh Blvd, Creve Coeur, MO 63141. The request will allow for a new building with three drive-through lanes. The subject property is zoned GC-General Commercial District, where Credit Unions (NAICS 522130) and All Drive-in and Drive-Through Services (excluding Food Services) (NAICS CC442100) are permitted with conditions for review by the Planning and Zoning Commission and final approval by the City Council.

**ADDITIONAL INFORMATION:** The Planning and Zoning Commission is scheduled to review and make a recommendation to City Council on the proposal on Monday, May 18, 2020. Meetings are held at 6:30 P.M., in the Council Chambers of the Creve Coeur Government Center located at 300 North New Ballas Road. Additional information regarding the proposal is available at the Government Center, Planning Division offices or on the City's website at www.crevecoeurmo.gov/447/Current-Planning-Projects.

Due to the pandemic emergency, Planning and Zoning Commission and City Council meetings will be held virtually until further notice. Online meetings are hosted through a remote conferencing service called Zoom, which offers audio and/or video conferencing. For the most up-to-date meeting information procedures, and how to participate, please refer to the City's website at www.crevecoeurmo.gov. We encourage you to attend remotely if you have any questions or wish to make a statement. In addition, you can submit written or email comments in advance of the meeting. For information about this proposal or to verify the meeting schedule, or for updated meeting procedures, please visit the City's website. You may also call (314) 872-2501 or e-mail wkelly@crevecoeurmo.gov.

**Key Issues:** 

- Does the request integrate with the existing surrounding uses?
- Does the request further or implement the goals of the Comprehensive Plan?
- Does the request meet the requirements for a Conditional Use Permit?

Comprehensive Plan References

• Lindbergh Boulevard

Zoning Code References

- Section 405.360: GC-General Commercial **Business District**
- Section 405.470: Conditional Uses
- Section 405.680: Lighting
- Section 1080: Site Concept, Site Development and Minor Site Plan Approval.

John Hopkins **APPLICANT:** 

Vantage Credit Union 4020 Fee Fee Road

**APPLICANT'S** Yosep Howley

**CEDC** REPRESENTATIVE:

10820 Sunset Office Drive, Suite 200

St. Louis, MO 63127





STAFF CONTACT: Whitney Kelly, AICP, City Planner

CC: Heather Silverman and Alexis Travers, Ward I

#### **AERIAL PHOTO**



611 N. Lindbergh Blvd., Creve Coeur, MO 63141.

#### PROJECT DESCRIPTION AND RATIONALE FOR CONDITINAL USE PERMIT


The proposed project involves the construction of a financial institution building to serve as a branch for Vantage Credit Union. The proposed building is single-story, 3,384 s.f. in floor area, and includes three (3) drive-thru lanes for PTM and teller service. The drive thru-lanes are proposed to be located on the south side of a building under an overhead canopy, attached to the building.

The site improvements include a landscaped berm in the southeast corner of the parcel, that will help to shield Lindbergh Blvd from headlights as cars utilize the drive-thru lanes. The berm provides visual protection for northbound and southbound vehicles, as well as vehicles entering or exiting the Sunswept neighborhood via the intersection of Lindbergh Boulevard and Sunswept Drive. New sidewalks will be added along Sunswept Drive and Lindbergh Boulevard.

The proposed site improvements will result in a lower amount of impervious surfacing than the previous restaurant site. The existing impervious percentage is 53% while the proposed impervious percentage is 34%. Proposed site improvements include a water quality infiltration basin, to be located to the west of the proposed building.

Landscape measures are proposed to meet Creve Coeur standards and provide adequate screening for adjacent properties. Existing trees located in the street right of ways and in the western portion of the site are proposed to remain where possible.

#### LEGEND SITE DEVELOPMENT PLAN EXISTING CONTOURS PROPOSED CONTOURS EXISTING STORM SEWER PROPOSED STORM SEWER EXISTING SANITARY SEWER VANTAGE CREDIT UNION RIGHT-OF-WAY MONSANTO EASEMENT WORLD CENTERLINE HEADQUARTERS HEADQUARTERS EXISTING TREE A TRACT OF LAND IN THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER OF EXISTING SPOT ELEVATION TEALWOOD(N) SECTION 1, TOWNSHIP 45 NORTH, RANGE 5 EAST PROPOSED SPOT ELEVATION SUNSWEPT(N) STORMWATER RUNOFF CALCULATIONS ST. LOUIS COUNTY, MISSOURI TEALWOOD(S) TO BE REMOVED T.B.R.& R. (15 Yr. / 20 Min. STORM) TO BE REMOVED & RELOCATED TO BE USED IN PLACE ADJUST TO GRADE TOTAL SITE AREA = 1.78 ac. BACK OF CURB **EXISTING RUNOFF CALCULATIONS** FACE OF CURB $0.94 \text{ ac.} \times 3.54 \text{ c.f.s./ac.} = 3.33 \text{ c.f.s.}$ \_\_\_\_w\_\_\_w WATER MAIN 0.84 ac. x 1.70 c.f.s./ac. = 1.43 c.f.s. 1.78 ac. 4.76 c.f.s. UNDERGROUND TELEPHONE **LOCATION MAP** OVERHEAD WIRE 0.08 ac. x 3.54 c.f.s./ac. 1 inch = 20 ftPAVEMENT: 0.53 ac. x 3.54 c.f.s./ac. = 1.88 c.f.s.—\_\_E\_\_\_\_E UNDERGROUND ELECTRIC 1.17 ac. x 1.70 c.f.s./ac. SILTATION CONTROL ● - DENOTES SET 1/2" x 18" REBAR FIRE HYDRANT WITH CAP STAMPED "MARLER L.S.-347-D" PROPERTY DATA POWER POLE O - DENOTES FOUND 1/2" IRON PIPE 4.15 c.f.s. - 4.76 c.f.s.= (-0.61) c.f.s. WATER VALVE + - DENOTES FOUND CROSS LIGHT STANDARD A - DENOTES FOUND RIGHT OF WAY MARKER OWNER = DEWOSKIN LIMITED PARTNERSHIP NO 2 **ADDRESS** = 611 N. LINDBERGH BLVD. CREVE COEUR, MO 63141 NOTES OF INTEREST LOCATOR NUMBER = 17M140010= GC GENERAL COMMERCIAL DISTRICT = 77,514 s.f. or 1.78 ACRES AREA (TOTAL) \ OVERHEAD ELECTRIC LINE. POWERPOLE AND GUY WIRE IS LOCATED OUTSIDE EASEMENT, WATER SHED = DEER CREEK AS SHOWN ON SURVEY. FIRE DISTRICT = CREVE COEUR 佗∖ SUBJECT'S LANDSCAPE AREA EXTENDS INTO PRIVATE DRIVE, AS SHOWN ON SURVEY. SCHOOL DISTRICT = LADUE SCHOOL DISTRICT (b) SUBJECT'S SIDEWALK EXTENDS INTO PRIVATE DRIVE, POSSIBLE CROSS ACCESS ELECTRIC SERVICE = AMERENUE EASEMENT, AS SHOWN ON SURVEY. É\ SUBJECT'S LANDSCAPE AREA EXTENDS INTO PRIVATE DRIVE, AS SHOWN ON SURVEY **GENERAL NOTES** 10'W WATER EASEMENT RECORDED IN DEED BOOK 3674, PAGE 279 IS NOT LISTED IN **N 89.09'30" W 359.99' (S)** 360.15'(R) TITLE COMMITMENT, AS SHOWN ON SURVEY) 1.) ALL UTILITIES SHOWN HAVE BEEN LOCATED FROM AVAILABLE RECORDS. THEIR LOCATION SHOULD BE CONSIDERED APPROXIMATE. THE CONTRACTOR HAS THE RESPONSIBILITY TO NOTIFY ALL UTILITY COMPANIES, PRIOR TO CONSTRUCTION, TO HAVE EXISTING UTILITIES FIELD LOCATED. THE CONTRACTOR SHALL BE ON RECORD WITH THE MISSOURI ONE CALL SYSTEM. ALL PROPOSED UTILITIES SHALL BE UNDERGROUND. SCHEDULE "B" TITLE EXCEPTION NOTES 2.) ALL ELEVATIONS ARE BASED ON BENCHMARK SHOWN. .) BOUNDARY AND TOPOGRAPHIC SURVEY BY MARLER SURVEYING CO. THIS SURVEY IS BASED ON A TITLE REPORT PREPARED BY CHICAGO TITLE INSURANCE COMPANY, .) ALL ON-SITE MATERIALS AND METHODS OF CONSTRUCTION TO MEET THE CURRENT STANDARDS AND SELECT TITLE GROUP, LLC COMMITMENT NO. STG-2019-09-2431-SOO, DATED AUGUST 20, 2019 AT SPECIFICATIONS OF THE CITY OF CREVE COUER, MODOT AND M.S.D. 5.) ALL GRADED AREAS SHALL BE PROTECTED FROM EROSION BY EROSION CONTROL DEVICES AND/OR SEEDING BACK OF WALL AND MULCHING AS REQUIRED BY THE CITY OF CREVE COEUR AND MODOT 6.) PRIOR TO BEGINNING ANY WORK ON THE SITE, THE SUBCONTRACTOR SHALL CONTAC CONTRACTOR FOR SPECIFIC INSTRUCTIONS RELEVANT TO THE SEQUENCING OF WORK. ITEMS NOT LISTED BELOW ARE STANDARD EXCEPTIONS AND/OR ARE NOT MATTERS OR ISSUES THAT RETAINING WALL-WITH SIDE INTAKE -2 GRATE INLFT . MOMUMENT 7.) GRADING CONTRACTOR SHALL INSTALL SILTATION CONTROL PRIOR TO STARTING THE GRADING. ADDITIONAL WITH SIDE INTAKE 10. EASEMENT GRANTED TO UNION ELECTRIC, AS SET FORTH IN INSTRUMENT RECORDED IN BOOK SILTATION CONTROL DEVICES SHALL BE INSTALLED AS DIRECTED BY THE CITY OF CREVE COUER AND MODOT. 5789 AT PAGE 149 (BENEFIT'S SUBJECT PROPERTY, SHOWN ON SURVEY), BOOK 4109 PAGE 69 8.) ALL FILLS AND BACKFILLS SHALL BE MADE OF SELECTED EARTH MATERIALS, FREE FROM BROKEN MASONRY, (BENEFIT'S SUBJECT PROPERTY, SHOWN ON SURVEY), BOOK 4109 PAGE 70 (DOES NOT BENEFIT ROCK, FROZEN EARTH, RUBBISH, ORGANIC MATERIAL AND DEBRIS. D.) GRADING CONTRACTOR SHALL KEEP EXISTING ROADWAYS CLEAN OF MUD AND DEBRIS AT ALL TIMES SUBJECT PROPERTY, NOT SHOWN ON SURVEY), BOOK 4044 PAGE 364 (BENEFIT'S SUBJECT O.) PROPOSED CONTOURS SHOWN ARE FINISHED ELEVATIONS ON PAVED AREAS. PROPERTY, SHOWN ON SURVEY) AND BOOK 4044 PAGE 365 (DOES NOT BENEFIT SUBJECT 1.) ALL GRADING AND DRAINAGE TO BE IN CONFORMANCE WITH THE CITY OF CREVE COUER AND M.S.D. PROPERTY, NOT SHOWN ON SURVEY), IN THE LAND RECORDS OF ST. LOUIS COUNTY, MISSOUR 12.) SIDEWALKS ALONG THE ACCESSIBLE ROUTE SHALL NOT HAVE A SLOPE EXCEEDING 1'V: 20'H. SLOPES 11. EASEMENT GRANTED TO METROPOLITAN ST. LOUIS SEWER DISTRICT. AS SET FORTH IN GREATER THAN 1'V:20'H MUST BE DESIGNED AS A RAMP. SIDEWALKS TO BE CONSTRUCTED TO ST. LOUIS INSTRUMENT RECORDED IN BOOK 3621 AT PAGE 403 (BENEFITED PARENT TRACT, NOT SHOWN O 13.) SIDEWALKS, CURB RAMPS, RAMPS AND ACCESSIBLE PARKING SPACES SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE CURRENT APPROVED "AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES" SURVEY) AND BOOK 5822 PAGE 334 (BENEFIT'S SUBJECT PROPERTY, SHOWN ON SURVEY), IN THE (ADAAG) ALONG WITH THE REQUIRED GRADES, CONSTRUCTION MATERIALS, SPECIFICATIONS AND SIGNAGE. II ENCLOSURE LAND RECORDS OF ST. LOUIS COUNTY, MISSOURI. ANY CONFLICT OCCURS BETWEEN THE ADAA GUIDELINES AND THE INFORMATION ON THE PLANS, THE ADAA PAVEMENT BICYCLE RACK ON-GUIDELINES SHALL TAKE PRECEDENCE AND THE CONTRACTOR SHALL NOTIFY THE PROJECT ENGINEER PRIOR 12. TERMS AND PROVISIONS OF EASEMENT TO USE AND EXTEND SUNSWEPT DRIVE, RECORDED TO ANY CONSTRUCTION. CONC. PAD (PROVIDE) 06/03/57, IN BOOK 3759 AT PAGE 505 (BENEFIT'S SUBJECT PROPERTY, SHOWN ON SURVEY), IN 3 BICYCLE PARKING 14.) NO GRADE SHALL EXCEED 3(H):1(V) UNLESS JUSTIFIED BY GEOTECHNICAL REPORT THAT HAS BEEN APPROVED THE LAND RECORDS OF ST. LOUIS COUNTY, MISSOURI. VERT. CURB BY THE CITY OF CREVE COEÙR. 15.) STORM WATER SHALL BE DISCHARGED AT AN ADEQUATE NATURAL DISCHARGE POINT. SINKHOLES ARE NOT PAVEMENT ADEQUATE NATURAL DISCHARGE POINTS. 16.) ALL LANDSCAPED AREAS TO BE FILLED WITH A MINIMUM OF 6" OF TOPSOIL 17.) ALL LANDSCAPED AREAS DISTURBED BY OFF-SITE WORK SHALL BE IMMEDIATELY SEEDED OR SODDED, IRECTED BY THE CITY OF CREVE COEUR OR MODOT UPON COMPLETION OF WORK IN THE AREA AFFECTED. 18.) ADEQUATE TEMPORARY OFF-STREET PARKING FOR CONSTRUCTION EMPLOYEES SHALL BE PROVIDED. PARKING LAND DESCRIPTION ON NON-SURFACED AREAS SHALL BE PROHIBITED IN ORDER TO ELIMINATE THE CONDITION WHEREBY MUD FROM CONSTRUCTION AND EMPLOYEES' VEHICLES IS TRACKED ONTO THE PAVEMENT CAUSING HAZARDOUS ROADWAY AND DRIVEWAY CONDITIONS. 19.) ALL SEWER CONSTRUCTION AND MATERIALS TO BE IN ACCORDANCE WITH THE METROPOLITAN ST. LOUIS SEWER DISTRICT STANDARD CONSTRUCTION SPECIFICATIONS FOR SEWER AND DRAINAGE FACILITIES, (LATEST A TRACT OF LAND IN THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 1, TOWNSHIP PROPOSED BUILDING 45 NORTH, RANGE 5 EAST, IN ST. LOUIS COUNTY, MISSOURI, FRONTING 215.36 FEET ON THE WEST LINE OF LINDBERGH BOULEVARD, BY A DEPTH WESTWARDLY BETWEEN PARALLEL LINES 20.) PARKING CALCULATIONS (PER ZONING SECTION 405.820) SINGLE STORY OF 360.15 FEET TO THE EAST LINE OF LOT 1 OF SUNSWEPT PLAT 3, ACCORDING TO THE PARKING REQUIREMENTS FOR BANKS 3,384 S.F. PLAT THEREOF RECORDED IN PLAT BOOK 87, PAGE 4 OF THE ST. LOUIS COUNTY RECORDS; For office Developments (including general offices, banks and savings and loans and other finance—related BOUNDED NORTH BY PROPERTY NOW OR FORMERLY OF MONSANTO CHEMICAL CO., SOUTH BY F.F. = 638.67 services, and medical and dental offices), the gross leasable floor area shall be interpreted as 85% of the THE NORTH LINE OF SUNSWEPT DRIVE 50 FEET WIDE. gross floor area of the entire building 2 GRATE IN GROSS FLOOR AREA -3,384 sf. x 85% = 2,876 sf. WITH SIDE INTAKE Four (4) parking spaces per one thousand (1,000) square feet of floor area: 2,876/1,000 \* 4 = 12 spaces TOTAL = 12 SPACES REQUIRED PARKING PROVIDED ON SITE = 26 SPACES (INCLUDES 2 ADA STALLS) MSD. BENCHMARK 13-15 ELEV.: 643.80' - "L" ON TOP OF NORTHEAST CORNER OF LOW BRICK WALL; 8' EAST OF SOUTH PILASTER OF ORNAMENTAL ENTRANCE TO SUNSWEPT SUBDIVISION ALONG LINDBERGH BOULEVARD. PROPERTIES OR ROADWAYS. ILLUMINATION LEVELS SHALL COMPLY WITH THE REQUIREMENTS OF THE CITY OF CREVE COEUR. THE SITE LIGHTING STANDARDS AND LOCATIONS SHALL BE REVIEWED AND APPROVED PER THE REQUIREMENTS OF THE CITY OF CREVE COEUR. LIGHTING DESIGN SUBJECT TO FINAL DESIGN OF LIGHTING ∕8' SIDEWALK 22.) LANDSCAPING SHALL COMPLY WITH THE REQUIREMENTS OF THE CITY OF CREVE COEUR. ------23.) ALL PROPOSED IMPROVEMENTS SHALL BE CONSTRUCTED TO THE CITY OF CREVE COEUR AND COIUNTY √6" CONC. 24.) ANY SIGNAGE PROPOSED FOR THIS SITE SHALL BE IN COMPLIANCE WITH THE ORDINANCES OF THE CITY OF VERT. CURB VERT. CURB ASPHALT CREVE COEUR. NORTH SUNSWEPT DRIVE PAVEMENT 25.) DENSITY CALCULATIONS -BERM FOR HEADLIGH SITE COVERAGE: The area of a non-residential site which is covered by buildings, driveways, parking lots, loading areas, but -2 GRATE INLET 2 GRATE INLETexcluding landscaped and green spaces, plaza, pedestrian circulation and unpaved buffer areas. WITH SIDE INTAKE . WITH SIDE INTAKE PARKING & DRIVE AISLES = 21,113 s.f.24,497 s.f.± $= 24,497 \pm s.f. / 77,514 s.f. \times 100 = 31.6\%$ SITE COVERAGE 26.) FLOOR AREA RATIO (F.A.R.) 3,384 s.f. BUILDING = 0.0477,514 s.f. SITE AREA 27.) ALL SIGNS AND BANNERS SHALL BE IN CONFORMANCE WITH ARTICLE VIII, SIGN REGULATIONS OF THE ZONING CODE. THE RELOCATION AND REPLACEMENT OF ALL SIGNS SHALL REQUIRE A PERMIT PER ARTICLE VIII SIGN REGULATIONS. ANY NON-CONFORMING SIGN AREAS MUST BE DOCUMENTED PRIOR TOT HE REMOVAL AND 28.) STRUCTURE SETBACKS (PER GENERAL COMMERCIAL ZONING) FRONT RAMP 29.) PARKING SETBACKS SUNSWEPT DRIVE (PRIVATE) (50'W) FRONT 10 FT. (SECT. 405.240) 30.) AN UNDERGROUND IRRIGATION SYSTEM SHALL BE INSTALLED AS REQUIRED PER SEC. 405.540(10). **ZONING NOTES** 31.) PARKING LOT LIGHTING SHALL BE DOWNCAST AND FULLY SHIELDED IN CONFORMANCE WITH SECTION 405.680, LIGHTING OF THE ZONING CODE. 32.) ALL SIGNS AND BANNERS SHALL BE IN CONFORMANCE WITH ARTICLE VIII, SIGN REGULATIONS OF THE ZONING CODE. THE RELOCATION AND REPLACEMENT OF ALL SIGNS SHALL REQUIRE A PERMIT PER ARTICLE VIII SIGN ZONED: "GC" GENERAL COMMERCIAL DISTRICT REGULATIONS. ANY NON-CONFORMING SIGN AREAS MUST BE DOCUMENTED PRIOR TOT HE REMOVAL AND FRONT SETBACK - 10' UNLESS PARKING IN FRONT OF BUILDING, THEN 50' SIDE SETBACK - 12' 33.) THE TRASH ENCLOSURE SHALL BE BUILT OF MATERIALS THAT ARE CONSISTENT WITH THE BUILDING, SUBJECT REAR SETBACK -TO THE ZONING ADMINISTRATOR'S APPROVAL. BUFFER YARD - 20' WHERE PROPERTY ADJOINS SINGLE FAMILY RESIDENTIAL DISTRICT EXISTING SITE CONDITIONS MAY FALL WITHIN PERMITTED USES AS LISTED IN THE CITY OF CREVE COEUR ZONING REGULATIONS, ZONING REGULATIONS ARE SUBJECT TO CHANGE, INTERPRETATION AND EXCEPTION, FOR FURTHER INFORMATION CONTACT THE CITY OF CREVE COEUR ZONING PLANNING AND ZONING DEPARTMENT AT (314) 432-6000. ZONING INFORMATION HAS BEEN COLLECTED BY THE LAND SURVEYOR AND CONSIDERED TO BE ACCURATE, HOWEVER THIS SHOULD BE VERIFIED BY THE CLIENT. SEE ITEM 6A UNDER TABLE A. FLOOD ZONE NOTES STANDARD UNIVERSAL — HANDICAP PARKING SIGN BY GRAPHIC PLOTTING ONLY, THIS PROPERTY DOES NOT LIE WITHIN ANY SPECIAL FLOOD ZONE AREAS ACCORDING TO THE FLOOD INSURANCE RATE MAP PANEL NUMBER 29189CO192K AND COMMUNITY NUMBER 290344 (CITY OF CREVE NOTE: COEUR) WHICH BEARS AN EFFECTIVE DATE OF FEBRUARY 4 2015. THE PROPERTY LIES WITHIN UNSHADED ZONE X (AREAS DETERMINED TO BE OUTSIDE 500 YEAR FLOOD PLAIN). THE UNDERGROUND UTILITIES HAVE BEEN PLOTTED FROM AVAILABLE SOURCES AND THEIR LOCATIONS MUST BE STANDARD "VAN 60" ABOVE FIN. GRADE CONSIDERED APPROXIMATE ONLY. THE VERIFICATION OF THE VAN ACCESSIBLE ACCESSIBLE" SIGN ACTUAL LOCATIONS OF ALL UNDERGROUND UTILITIES, EITHER REQ'D AT VAN SHOWN OR NOT SHOWN ON THIS DRAWING, SHALL BE THE ACCESSIBLE SPACES RESPONSIBILITY OF THE CONTRACTOR AND SHALL BE LOCATED Prepared For: 9.00' 9.00' SECTION A-A 1:12 SLOPE FLARES MAX PRIOR TO GRADING OR CONSTRUCTION OF IMPROVEMENTS. MOUNTING POST \_\_\_\_ 2"∼ GALV. John Hopkins ·8:00'· Call BEFORE you DIG Chief Risk Officer FINISHED GRADE 1:12 SLOPE \_ **TOLL FREE** 1-800-DIG-RITE Vantage Credit Union SECTION B-B MISSOURI ONE-CALL SYSTEM, INC. -3500 PSI CONCRETE PAINT GRAPHIC ON PAVING PREPARED BY: @ H.D.C.P. STALLS MISSOURI ONE CALL TICKET NUMBER 192593728 UTILITIES CONTACT BY MISSOURI ONE CALL WERE: HANDICAP SIGN ADB COMPANIES TYPICAL PARKING STALLS AMEREN MISSOURI ELECTRIC AU DISTRIBUTION HANDICAP RAMP DETAIL CHARTER COMMUNICATIONS CIVIL ENGINEERING 314.729.1400 Fax: 314.729.1404 LEVEL 3 NOW CENTURYLINK MISSOURI AMERICAN WATER CO HANDICAP PARKING SIGN **DESIGN CONSULTANTS** www.cedc.net SPIRE MO EAST ST LOUIS METROPOLITAN SEWER



PROFESSIONAL ENGINEER CEDC LICENSE NO.: 2003004674

Proj. # 1984 No. Description


CUP SUBMITTAL 04/17/20

**DEVELOPMENT** PLAN

SITE

DRAWING NO.

BASE MAP: 17M1



5 gal

18"-24"

24"-30'

5 Gal.

5 gal

5 gal

SIZE

| gal

SIZE

|5 qa|

SIZE

2 Qt. @ 18" OC

| Ga| @ 30" 0C

2 Qt. @ 24" OC

2 Qt. @ 24" OC

Plug at 18" OC

Plug at 18" OC

Plug at 18" 00

Plug at 18" OC

Green Velvet Boxwood / Buxus 'Green Velvet'

Purple Coneflower / Echinacea purpurea 'Magnus'

Party Favor Rose Mallow / Hibiscus Iasiocarpos

|Winter Gem Boxwood / Buxus microphylla 'Winter Gem'

| 'Hummingbird' Summersweet / Clethra alnifolia 'Hummingbird'

|Happy Returns Daylily / Hemerocallis hybrid 'Happy Returns'

Foerster's Reed Grass / Calamagrostis acutifolia 'Karl Foerster

Ruby Slippers Hydrangea / Hydrangea quercifolia 'Ruby Slippers'

|Northern Bayberry / Myrica pensylvanica |

Hicks Yew / Taxus media 'Hicksii'

COMMON / BOTANICAL NAME

|COMMON / BOTANICAL NAME

COMMON / BOTANICAL NAME

QTY COMMON / BOTANICAL NAME

Golden Alexander / Zizia aurea

Rose Turtle-Head / Chelone obliqua

Swamp Milkweed / Asclepias incarnata

Brown Fox Sedge / Carex vulpinoidea

Great Green Bulrush / Scirpus atrovirens

|Morning Star Sedge / Carex grayi

Palm Sedge / Carex muskingumensis

|Lenten Rose / Helleborus orientalis

ANNUALS/PERENNIALS QTY

GRASSES

NATIVE GRASSES

CALA

- WILL BE PROVIDED AS A CONDITION OF DEVELOPMENT (By Others)

#### # OF PLANTS SPACING "D" ROW "A" PER SQ. FT. 20.8 0.25 15.6" 0.45 AS SHOWN 10.4" 1.00 1.44 8.66" 6.93" 2.25 SET AT ORIGINAL PLANTING DEPTH SEE PLANTING PLAN FOR SPACING

-SUBGRADE

\_2" DEEP MULCH - KEEP MULCH

AWAY FROM CROWN OF PLANT

PLANTING SOIL MIX

SECTION

ROTO-TILL

PER NOTES

BED TO DEPTH

FORB/GRASS PLANTING DETAIL N.T.S.



- DO NOT CUT CENTRAL LEADER

DOUBLE STRAND 12 GAUGE WIRE

PAINTED FLUORESCENT ORANGE

COVERED W/2-PLY RUBBER HOSE

3 INCHES SHREDDED BARK MULCH

-8' STEEL TEE POST, SET PLUMB

8" 2-PLY RUBBER HOSE

WHITE FLAGGING (TYP.)

4 INCH DEEP SAUCER

UNDISTURBED SUBSOIL

FROM TOP 1/3 OF THE BALL

AFTER PLACEMENT IN PIT

TREE WRAP

BACKFILL MIX

- CROWN OF ROOT BALL SHALL BEAR SAME RELATION

OF BURLAP. REMOVE ANY NON-BIODEGRADABLE MATERIAL

(OR SLIGHTLY ABOVE) TO FINISHED GRADE AS IT

- PREPARED ADMIXTURE BACKFILL OR NATIVE SOIL

-CREATE SOIL SAUCER W/ TOPSOIL-6" MINIMUM

DECIDUOUS TREE PLANTING

BORE TO PREVIOUS GRADE

PREPARED SOIL BACKFILL

SET SHRUB ROOT BALL I" HIGHER

-3 INCHES MULCH

-BACKFILL MIX

SHRUB IS B & B, THEN

REMOVE BURLAP & ROPE

FROM TOP 1/3 OF BALL

UNDISTURBED SUBSOIL

THAN ADJACENT FINISH GRADE

-3" MINIMUM BARK MULCH

PLANT PINE VARIETIES TOP OF BALL AT 4"

ABOVE SURROUNDING GRADES.

2X BALL DIAMETER

- 1.) All natural vegetation shall be maintained where it does not interfere with construction or the permanent plan of operation. Every effort possible shall be made to protect existing structures or végetation from damage due to equipment usage. Contractor shall at all times protect all materials and work against injury to public.
- 2) The landscape contractor shall be responsible for any coordination and sequencing with other site related work being performed by other contractors. Refer to additional drawings for further coordination of work to be done. 3.) Underground facilities, structures and utilities must be considered
- approximate only. There may be others not presently known or shown. It shall be the landscape contractor's responsibility to determine or verify the existence of and exact location of the above (Call utility location services in municipality). 4.) Plant material are to be planted in the same relationship to grade as was grown in nursery conditions. All planting beds shall be
- cultivated to 6" depth minimum and graded smooth immediately before planting of plants. Plant groundcover to within 12" of trunk of trees or shrubs planted within the area. 5.) It shall be the landscape contractor's responsibility to: A.) Verify all existing and proposed features shown on the drawings prior to commencement of work.
- B.) Report all discrepancies found with regard to existing conditions or proposed design to the landscape architect immediately for a decision. C.) Stake the Tocations of all proposed plant material and obtain the approval of the owner's representative or landscape architect
- ten (10) days prior to installation. 6.) Items shown on this drawing take precedence over the material list. It shall be the landscape contractor's responsibility to verify all quantities and conditions prior to implementation of this plan. No substitutions of types or size of plant materials will be accepted without written approval from the landscape architect. 7.) Provide single-stem trees unless otherwise noted in plant schedule. 8.) All plant material shall comply with the recommendations and requirements
- of ANSI Z60.1 "American Standards for Nursery Stock". 9.) It shall be the contractor's responsibility to provide for inspection of the plant material by the Landscape Architect (or Owners' Representative) prior to acceptance. Inspections may take place before, during or after installation. Plants not conforming exactly to the plant list will not be accepted
- and shall be replaced at the landscape contractor's expense. 10.) All bids are to have unit prices listed. The Owner has the option to delete any portion of the contract prior to signing the contract or beginning work. This will be a unit price contract; quotes shall be valid for 12 months.
- II.) Should auger equipment be utilized in excavating any plant pits, vertical sides of plant pits shall be thoroughly scarified to avoid creation of "polished side walls" prior to plant material installation. REMOVE BURLAP, WIRE & ROPE 12.) All excess topsoil, rocks, debris and/or tainted soils shall be removed
  - by the general contractor prior to point project is turned over to the landscape contractor to commence landscape installation. 13.) Keep all plant material (except turf) a minimum of 36" clear of fire hydrants.
  - 14.) Landscape contractor shall kill \$ remove all existing weeds within the project site. 15.) All tags, nursery stakes, labels, etc. shall be removed by the landscape contractor at completion of all landscape installation. 16.) Landscape contractor shall be in compliance with all federal, state and local
  - laws / regulations relating to insect infestation and/or plant diseases. 17.) All substitutions of plant material shall be submitted to landscape architect for PRUNING:
  - 1.) Lightly prune trees at time of planting. Prune only the crossover limbs, intermingled leaders and/or any broken branches. Some interior twigs and lateral branches may be pruned. However, do not remove the terminal buds of branches that extend to the edge of the crown. 2.) All pruning shall comply with ANSI A300 standards.
  - 1.) The landscape contractor shall submit certificates of insurance for workman's compensation and general liability.

## 1.) All mulch to be shredded oak bark mulch at 3" depth (after

- compaction) unless otherwise noted. Mulch shall be clean and free FOLD DOWN BURLAP @ TOP OF ROOT BALL & REMOVE TOP 1/3 of all foreign materials, including weeds, mold, deleterious materials, etc. 2.) No plastic sheeting or filter fabric shall be placed beneath shredded bark mulch beds. Mirafi fabric shall be used beneath all gravel mulch beds. Lap fabric 6" over adjacent coverages. 3.) Edge all beds with spade-cut edge unless otherwise noted.
  - MAINTENANCE:

INSURANCE:

- 1.) Landscape Contractor shall provide a separate proposal to maintain all plants, shrubs, groundcover, perennials and annuals for a period of 12 months after acceptance.
- 2) Contractor shall ensure that only competent and trained personnel shall provide such services and that such services be provided in a timely 3.) Watering of seeded or sodded lawns shall begin immediately and shall
- continue to be provided continuously for the following 72 hours. Regardless, the landscape contractor shall be resposible for all landscape maintenance until project turnover. SIGHT TRIANGLES:
- 1.) No landscape material or other obstructions shall be placed or be maintained within the sight distance area so as not to impede the vision between a height of thirty inches (30") and ten feet (10') above the adjacent street or paving surfaces.
- 2.) Sight triangles at the intersection of a public street and a private access way (except for single family residences) shall also be formed by measuring from the point of intersection of the street frontage curbs and the entrance curb lines a distance of 35' and connecting the points so established to form the sight triangle area.
- 1.) Topsoil mix for all proposed landscape plantings shall be five (5) parts well-drained screened organic topsoil to one (1) part
- Canadian sphagnum peat moss as per planting details. Roto-till opsoil mix'to ā deṗth of 6" minimu'm aṅd građe smooth.
- 2) Provide a soil analysis, as requested, made by an independent soil-testing agency outlining the % of organic matter, inorganic matter, deleterious material, pH and mineral content.
- 3.) Any foreign topsoil used shall be free of roots, stumps, weeds, brush, stones (larger than I"), litter or any other extraneous or toxic material. Landscape contractor shall be fully responsible for correcting all negative soil issues prior to plant installation. Killing and removal of all weeds shall be the responsibility of the landscape contractor as part of this task
- 4.) Landscape contractor to apply pre-emergent herbicide to all planting beds upon completion of planting operations and before application of shredded bark mulch.
- 5.) Install siltation controls prior to commencement of any grading operations. Inspect and maintain all siltation fences on a weekly basis until vegetation is established.


## 1.) Provide stakes and deadmen of sound, new hardwood, free

shall be used.

- 2.) Tree wrap tape shall be 4" minimum, designed to prevent borer damage and winter freezing. Additionally, only 3-ply tying material
- All disturbed lawn areas to be seeded with a mixture of Turf-Type fescue (300# per acre) and bluegrass (18# per
- acre). Lawn areas shall be unconditionally warranted for a period of 90 days from date of final acceptance. Bare areas more than one square foot per any 50 square feet shall 2.) Seed and fertilization operations shall occur between May 1
- and June 15th or between September I and October 15th unless directed by others in writing AND irrigation system is operating. 3.) Granular or pelleted fertilizer consisting of 50% water-insoluble slow release nitrogen, phosphorous and potassium in a 12-12-12
- 4.) The turf contractor shall be responsible for protection of finished grade; restore and repair any erosion or water damage and obtain
- owners' approval prior to seeding or sod installation. 5.) Landscape contractor shall offer an alternate price for sod in lieu of seed. Sod shall be cut at a uniform thickness of 3/4". No broken pieces, irregular pieces or torn pieces will be accepted. 6.) Any points carrying concentrated water loads and all slopes of 15% or greater shall be sodded.
- 7.) All sod shall be placed a maximum of 24 hours after harvesting. 8.) Recondition existing lawn areas damaged by Contractor's operations including equipment/material storage and movement of vehicles. 9.) Sod Contractor to ensure sod is placed below sidewalk and all
- paved area elevations to allow for proper drainage WARRANTY: I.) All plant material (excluding ground cover, perennials and annuals)
- are to be warranted for a period of 12 months after complete installation of all landscape material at 100% of the installed price. 2.) Any plant material found to be defective shall be removed and replaced
- within 30 days of notification or in growth season determined to be best for 3.) Only one replacement per tree or shrub shall be required at the end of the warranty period, unless loss is due to failure to
- comply with the warranty. 4.) Lawn establishment period will be in effect once the lawn has been mowe'd three times. Plant establishment

period shall commence on the date of acceptance and

100% completion. 5.) A written guarantee shall be provided to the owner per conditions outlined in #1 above.



SPADE-CUT EDGE DETAIL

DRAWN R. MARDIS CHECKED RWM/EL DATE 4/14/2020 SCALE 1"=20'-0" 2020-122 SHEET















## Keynote Legend:


- Brick Veneer: BRK-01 Cloud Ceramics "Ebony IS" Velour (Modular), running bond with SGS 22X Tan mortar.
- 2 Aluminum Composite Material Rainscreen: ACM-01 Alpolic "MTLC BSX SILVER" 4-BSX3.5.
- (3) MEG Wall Panel, Rainscreen. Color: # 758. Finish: SEI
- (4) Prefabricated Metal Canopy: Finish to match ACM-01.
- 5 Omitted.
- 6 Prefabricated Metal Coping: Finish to match BRK-01, Una-clad Mansard Brown or approved Equal.


- Prefabricated Metal Coping: Finish to match BRK-01.
- Prefabricated Metal Ladder: Prime & paint metal to match BRK-01.
- Aluminum Storefront & Glazing System: 2" x 4 1/2" clear anodized aluminum storefront with 1" insulated glazing. Provide PPG Solarban 60 Clear on Clear glazing base bid. Option 02 glazing: provide PPG Solar Ban 60 w/ Starphire low iron glass.
- Roof Top Unit Mechanical Screen: Cityscapes Envisor RTU screen: Design Option: Vertical; Panel Style: Louver; Trim Option: Alamo; Color Option: Mansard Brown.
- Signage by Others: Signage to be meet all city signage requirements and approved under separate process in accordance with the City of St. Peters.

- (12) Drive-up ATM and/or PTM.
- 4" diameter concrete filled steel bollards painted to match PTM machines.
- Masonry Control Joint: 3/8" masonry control joint filled w' continuous sealant (color to match mortar) & closed cell foam backer rod.









**NORTH ELEVATION** 



6400 W. Main St., Ste 1Q Belleville, IL 62223 (618) 623-9252

14205 W. 95th Street Lenexa, KS 66215 (913) 378-9533

143 W. Clinton Place St. Louis, MO 63122 (314) 965-7445



